HYUNDAI IT CORP.

Outdoor Type

H460SC

▶ Key Feature

- Sunlight Proof : Optical Bonding
- Anti – Vandal Protection
- All Weather Proof
- Ultra High Brightness
- IP 55/IP 64/IP 65 Confirmity

▶ Specification

Display Panel	Screen Size		46"
	Active Display Area (㎜)		1018.35 x 572.54
	Number of Pixels		1366 x 768 (WXGA)
	Aspect Ratio		16 : 9
	Display Colors		16.7 Mil
	Brightness (cd/㎡)/(typ)		2500
	Contrast Ratio		4000 : 1
	Response Time (ms, GTG)		8
	Viewing Angle (H˚/V˚)		178°/178°
	Bezel Size (U/D/L/R) (㎜)		11/11/11.5/11.5
	Out Line Dimension (㎜)		1047.4 x 600.6 x 63.8
	Weight (㎏)		16
	Life Time		30,000h
	Backlight type		LED
Connectivity& Control	Input	VGA (15pin D-Sub)	1
		HDMI	Option
	Network Connections	Wired	1
		Wireless	Option
	Power Requirement	Operating Voltage	100 - 240VAC
		Consumption (typ) (W)	530W (Max 2.0KW)
	Auto Cooling System		Yes
	Auto Heating System		Yes
Feature	Anti-Vandal Glass		Yes
	Touch Screen		Yes (Capacitive)
Mechanical	Dimension (mm)	Set (W x H x L) (㎜)	700 x 1595 x 235
		Active (W x H x L) (㎜)	572 x 1015 x 79
		Tempered Glass Thickness (㎜)	11.5
	Weight (kg)	Set Weight (㎏)	79
	Surface treatment	Surface treatment visible surfaces	Powder coated, Powder salty
	Accessories	Mounting (Bottom mounting)	M12 wedge anchor (8 pcs)
Environmental conditions	Max Temperature operational (℃)		50
	Min Temperature operational (℃)		-40
	Max Temperature storage (℃)		60
	Min Temperature storage (℃)		-20
	Humidity (non-condensing) (%)		10 - 90
Approvals	EMI/EMC		FCC, CE
	Safety		cTUVus, TUV, CB
	International Protection		IP55 - IP65
Computer			Option

All specifications are subject to change without prior notice

www. hyundaiit.com